

- **Exclusive movementless design resists shock and vibration – no gears to wear or misalign resulting in increased instrument life**
- **Gas-operated molecular sieve**
- **No elevation error**
- **Mercury free**
- **One bulb size for all ranges**
- **±1% full-span accuracy**
- **Maxivision® dial**
- **Readily available – two to three weeks delivery**
- **Limited five-year warranty**

A black-coated aluminum case with excellent impact resistance. Threaded ring permits adjustment. Available in 4½" and 6" sizes.



SELECTION TABLE

600A — 03		— C02		— B01		— A1		— L07		— AK			
Table 1		Table 2		Table 3		Table 4		Table 5		Table 6			
CASE STYLE		CASE SIZE		MOUNTING				ARMOR STYLE		LINE LENGTH		RANGES	
CODE	DESCRIPTION	CODE	SIZE	MOUNTING		CONNECTION		CODE	DESCRIPTION	CODE	LINE LENGTH	CODE	SINGLE RANGES
				SURFACE	FLUSH	LOWER	REAR						
03	ALUMINUM THREADED RING	C02	4½"	✓		✓				L01	5'	AB	-320/200°F
		C15	6"	✓		✓		A1	Stainless Steel Spring			AE	-100/100°F
										L03	10'	AG	-40/180°F
										L07	20'	AK	20/240°F
												AL	50/300°F
										L09	30'	AN	50/550°F
												AR	50/750°F
										L13	50'	AT	400/1200°F
												AY	-200/100°C
										L19	80'	BL	-80/40°C
												BN	-40/80°C
												BS	0/120°C
												BT	10/150°C
												BU	0/300°C
												BW	0/400°C
												BJ	200/650°C
												DUAL RANGES	
												CE	20/240°F 0/120°C
												CF	50/550°F 0/300°C
												DR	50/300°F 10/150°C
												DT	-40/180°F -40/80°C

*Minimum recommended insertion length ("u" dimension) in liquids is 4 inches and in gases is 6 inches for standard 3/8 x 3" bulb

TO ORDER THIS DURATEMP 600A-03 THERMOMETER:

Select:

1. Case Style: Aluminum/Threaded Ring _____ Table 1 _____ **600A 03**

2. Case Size & Mounting: 4½" Surface, Lower _____ Table 2 _____ **C02**

3. Bulb Style: 12" Bendable Extension with Union Connection _____ Table 3 _____ **B01**

4. Armor Style: Stainless Steel Spring _____ Table 4 _____ **A1**

5. Line Length: 20 feet _____ Table 5 _____ **L07**

6. Temperature Range: 20/240°F _____ Table 6 _____ **AK**

7. Options: Stainless Steel Tag _____ (See Page 210) _____ **XNH**

Consult factory for guidance in product selection
Phone (203) 385-0217, Fax (203) 385-0602 or
visit our web site at www.ashcroft.com